



Hula 46. Barstool with upholstered seat or oak wood and injection swivel central base, adjustable height, and finished in different colors.

0.14 m3 4.94 Ft 6.7 kg 14.77 Lbs

|               | Backrest height | Seat height | Width | Depth |
|---------------|-----------------|-------------|-------|-------|
| Measures (mm) | 655             | 680         | 485   | 460   |

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame           | Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Seat            | Upholstered seat with flame retardant polyurethane flexible foam with a density between 25 kg/m3 and 40 kg/m3, oak or walnut wood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Accesories      | Felt glide.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Other materials | Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Leather         | <div>                         Leather / Piel                     </div> <div>                         L1 High grade cow leather<br/>                         Piel de vaca de 1ª categoría                     </div> <div>                         L3 Polished full grain leather<br/>                         Plena flor pulida                     </div> <div>                         L6 Aniline leather batique-effect.<br/>                         Scandinavian cattle.<br/>                         Piel anilina efecto batique.<br/>                         Ganado escandinavo.                     </div> |

Premium finish  
 and wood  
 lacquers



Wood finish Oak



Aluminum finish



RESISTANCE AND  
 QUALITY

UNE-EN 16139:2013

FIREPROOF

UNE-EN 1021-1:2006  
 B.S. 5852 Part 2 Crib V  
 California Tech.Bulletin 117  
 BKZ 5.2

SUSTAINABILITY

FSC  
 ISO 14001  
 level® 2 certified to ANSI/BIFMA e3 Standard